

DBI565PXXLS.U Built-in undercounter dishwasher

General description

Turbo Combi Drying Product line: Logic Mode of installation: Built In Size: XXL Number of baskets: 3 Number of place settings: 16 place settings Upper basket type: Exclusive Lower basket type: Exclusive Removable cutlery basket for easy unloading

Construction

- Welded stainless steel container
- Exterior float detects water leakage on the base
- Stand by water protection
- Anti-block drain pump
- 8 Steel[™] Construction
- Hidden heater
- SCS+ Super Cleaning System+™
- Sensi Clean[™] Sensor measures dirtiness level
- Number of spray arms: 3
- Number of spray zones: 9
- Turbo Combi Drying
- Automatic door opening
- Cutlery Power Zone extra dishwashing power for the cutlery basket

Use and flexibility

- Number of place settings: 16 place settings
- Number of baskets: 3
- Upper basket type: Exclusive
- Upper basket system: Easy height adjustable with lever
- Guide rails with ball bearings for upper basket
- China Guard protects fragile load from the rotating spray arm
- Lower basket type: Exclusive
- Vase and bottle holder
- Tight mesh base in the baskets
- Removable cutlery basket for easy unloading
- 2 interior LED lights
- Required inlet water pressure: 0,03-1 MPa

Interaction & control

- Display Type: LCD display
- Ability to create own programs: Memory program
- Number of programs: 9
- Number of options: 8
- Status Light[™]
- Time remaining indicator: Yes
- Cycle end indication: Displayed with sound and light
- Adaptable power zones
- Adaptable water pressure
- , adptable mater processe

Programs

- 9 programs: Normal wash; Automatic program; Intensive program; Time program; Rinse and hold; Quick Pro wash; Self-cleaning; Sanitize; Anti odour
- Delayed start: 1-24 hours
- Green mode
- Speed mode
- Night mode
- Heat boost mode
- Normal mode

Design & integration

- From front adjustable rear foot
- Trim kit
- Multi fit outlet hose
- Simplified installation with integrated anti-siphon
- Depth (incl. wall spacing): 21 7/8" (555 mm)
- Height setting: 2 1/16" (53 mm)
- Possible adjustment of kick plate: 1 3/16 3 10/16" (30-94 mm)



Safety & Maintenance

- Aqua Safe™
- . Kid Safe™ lockable controls
 - Rinse-aid indication: Notification in display

Technical data

- Hot or cold water connection 9/16
- Max. temperature of inflow water: 140 F
- Noise level: 40 dB(A)
- Duration of normal wash cycle: 125 min 0
- Estimated annual energy consumption: 220 kWh .
- Energy consumption/cycle: 1 kWh •
- Estimated annual water consumption: 647 US Gal Water consumption/cycle: 3 US Gal .
- .
- Consumption in standby mode: 0.5 W
- Connection rating: 1300 W .
- Number of phases: 1 •
- . Current: 15 A
- . Frequency: 60 Hz
- . Required inlet water pressure: 0,03-1 MPa
- . Net weight: 97 lbs

Dimensions


- Width: 23 15/16" (608 mm)
- Height: 34 5/16" (871 mm)
- Depth: 21 13/16" (554 mm)
- Maximum product height: 36 3/8" (924 mm)
- Cord length: 71 7/16" (1815 mm)
- Depth with door open: 48 7/16" (1231 mm)
- Length of inflow hose: 64 3/16" (1630 mm)
- Length of outflow hose: 90 9/16" (2300 mm)

Logistic information

- Packaging width: 25 3/16" (640 mm)
- Packaging height: 36 5/8" (930 mm)
- Packaging depth: 26 15/16" (685 mm)
- Total weight of packaged product: 104 lbs Code: 742930
- •
- EAN code: 3838782774546 •
- Market: Domestic
- Range: Logic



Measurements: inches / millimetres



DW60 Built-in Dishwasher XXL USA

